HP ScanJet Pro 2000 s1 Sheet-feed Scanner



Fast, affordable, and designed to handle everything from simple color jobs to complex workflows. Quickly and reliably digitize larger projects with scan speeds up to 30 ppm/60 ipm and a 50-page ADF. Recommended for 2,000 pages per day.





Small size. Fast scans. Same reliable results.

- Produce scans at up to 30 ppm/60 ipm with two-sided scanning that captures both sides at once.
- Free up space for work. This HP ScanJet Pro is small and slim—a modern design perfect for the desktop.
- Don't wait for warm-up—HP Instant-on Scanning lets you begin scanning quickly.
- Load up to 50 pages into the automatic document feeder for fast, unattended scanning.



Optimize workflows with one-touch scanning

- Streamline routine work with one-touch scanning—create one-button, custom settings for recurring scan jobs.
- Scan images directly into applications with included and full-featured TWAIN and ISIS®.
- Easily transfer scans into editable text, secure PDF files, and more file types, using built-in OCR.
- Quickly share or archive scans directly to popular cloud destinations with HP Scan software.



Capture business documents like a pro

- Define scan profiles for common document types, and scan to multiple destinations with HP Scan software.
- Capture and organize documents, business cards, and other file types with feature-rich software.
- Produce clear, legible scans—up to 600-dpi resolution.

Scan speed measured at 300 dpi (black-and-white, grayscale, and color). Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.

Technical specifications

Scan Technology	CMOS CIS		
Scan Type	Sheetfed; Color Scanning: Yes		
Scan speed ADF (letter)	Up to 30 ppm/60 ipm		
Task speed	10×15 cm $(4 \times 6$ in) color photo to file (200 dpi, 24-bit, tiff): about 6.90 sec for single image scan; 10×15 cm $(4 \times 6$ in) color photo to e-mail $(150 \text{ dpi}, 24\text{-bit})$: about 9.13 sec for single image scan; 10×15 cm $(4 \times 6$ in) color photo to e-mail $(150 \text{ dpi}, 24\text{-bit})$: about sec for single image scan; 10×15 cm $(4 \times 6$ in) color photo to e-mail $(150 \text{ dpi}, 24\text{-bit})$: about sec for single image scan; 10×15 cm $(4 \times 6$ in) color photo to e-mail $(150 \text{ dpi}, 24\text{-bit})$: about 12.98 sec for single image scan		
Scan Resolution	Hardware: Up to 600 dpi (color and mono, Sheet-feed) Optical: Up to 600 dpi (color and mono, Sheet-feed)		
Scan File Format	For text & images: PDF, JPEG, PNG, BMP, TIFF, Text (.txt), Rich Text (rtf) and Searchable PDF		
Scan Input Modes	One default scan mode on front-panel for HP scan in Win OS, HP Easy Scan/ICA in Mac OS and third parties applications via TWA ISIS and WIA		
Scanner Advanced Features	Auto-color detect, auto-crop, auto-exposure, auto orient, OCR, edge removal, background cleanup, remove hole, color drop out straighten the page, scan to cloud, scan to email, PDF security		
ENERGY STAR Qualified	Yes		
Output Resolution Dpi Settings	75; 150; 200; 240; 300; 400; 500; 600; 1200 ppi		
Bit depth / Grayscale levels	24-bits external 48-bits internal; Grayscale Levels: 256		
Scan Size	ADF: 216 x 863 mm		
Media Types	Cut Sheet Paper, Printed Paper (Laser and ink), Pre-Punched Paper, Bank Checks, Business Cards, Freight Bills, Carbonless forms, Previously stapled media with staple removed, Plastic cards (up to 1.24mm)		
Media Size, ADF	$U.SLetter: 215.9 \times 279.4 \text{ mm } (8.5 \times 11 \text{ in}); U.SLegal: 215.9 \times 355.6 \text{ mm } (8.5 \times 14 \text{ in}); U.SExecutive: 184.2 \times 266.7 \text{ mm } (7.2 \times 10.5 \text{ in}); ISO A4: 210 \times 297 \text{ mm } (8.3 \times 11.7 \text{ in}); JIS B5: 182 \times 257 \text{ mm } (7.2 \times 10.1 \text{ in}); ISO B5: 176 \times 250 \text{ mm } (7.0 \times 9.9 \text{ in}); ISO A5: 148 \times 210 \text{ mm } (5.8 \times 8.3 \text{ in}); ISO A6: 105 \times 148 \text{ mm } (5.8 \times 4.1 \text{ in}); ISO A7: 74 \times 104 \text{ mm } (2.9 \times 4.1 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ mm } (2.0 \times 2.9 \text{ in}); ISO A8: 52 \times 74 \text{ in}; ISO A8: 52 \times 74 \text$		
Media weight (ADF)	50 to 180 g/m2		
Auto document feeder capacity	50 sheets of 75 g/m² paper		
Duty Cycle (Daily)	Recommended for 2000 pages per day		
Standard connectivity	USB 2.0 (Hi-Speed)		
Memory	64 MB		
Processor Speed	120 MHz		
Control Panel	Scan button, Power button with a LED and a LED for Error indication		
Image Scaling or Enlargement Range	Will not perform any arbitrary scaling.		
Twain Version	Windows: TWAIN version 2.1; Mac: n/a		
Software Included	Win: HP WIA scan driver, HP TWAIN scan driver, HP Scan, HP Scanner Tools Utility, Nuance PaperPort (Win only), I.R.I.S Readiris, I.R.I.S Cardiris (Win only), EMC ISIS (Win only)		
Compatible Operating Systems	OS X Mavericks 10.9, OS X Yosemite 10.10, OS X El Capitan 10.11, Microsoft® Windows® 10, 8.1, 8, 7: 32-bit or 64-bit		
Minimum System Requirements	PC: Apple® OS X Yosemite, OS X Mavericks, OS X Mountain Lion; 1 GB HD; Internet required; USB; Microsoft® Windows® 10, 8.1, 7: 32-bit or 64-bit, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Microsoft® Internet Explorer Mac: Apple® OS X Yosemite, OS X Mavericks, OS X Mountain Lion; 1 GB HD; Internet required; USB		
Operating environment	Operating Humidity Range: 15 to 80% RH (non-condensing) Non-operating Humidity Range: 0 to 90% RH (non-condensing) Recommended Humidity Operating Range: 15 to 80% RH (non-condensing) Operating Temperature Range: 10 to 35 ° C Recommended Operating Temperature Range: -40 to 60 ° C Recommended Operating Temperature Range: 10 to 35 ° C		
Power	Power Supply Type: External Power Adapter Power Consumption: 3.6 Watts (ready), 1.0 Watts (sleep), 0.1 Watts (auto-off), 0.1 Watts (off) Power Requirements: Input Voltage range: 90 - 264 VAC, Rated Frequency: 50 - 60HZ, Worldwide use		
Dimensions (W x D x H)	300 x 172.9 x 152.1 mm		
Weight	2.6 kg		
What's in the box	HP ScanJet Pro 2000 s1 Sheet-feed Scanner; Install guide; Support flyers; Warranty cards; 2 CDs; Power cords; Power adaptor; USB cables (All regions)		
Warranty	1 Year Limited Warranty (Return to HP/Dealer - Unit Exchange)		
Electromagnetic emission standard	Class B Emissions; CISPR 22:2008 (International); European Union EMC Directive 2014/30/EU, EN 55022:2010 (CE mark); China GB9254-2008 (CCC); Taiwan CNS13438:2006 (BSMl); USA CFR47 Part 15, Subpart B (FCC); ICES-003:2012 Issue 6 (Ganada); Australia C-tick (Includes New Zealand); KN 22 and Korea KCC; EAG EMC Certificate; Ukraine EMC approval; EN 61000-3-2:2014 (harmonics); EN 61000-3-3:2013 (flicker); Immunity CISPR 24:2010, EN 50024:2010		
Safety Approvals and Requirements	IEC 60950-1:2005 +A1+A11+A12 and all applicable amendments; CSA/UL 60950-1, 2nd edition (2007); EN 60950-1:2006 +A11 +A1 +A12+A2; EAC safety; Canada cUL CoC; China CCC; European Union CE; Kenya PVOC; Kuwait TER; Nigeria SON; Saudi Arabia SASO; South Africa NRCS; Taiwan BSMI; Ukraine safety approval		
Accessories	HP ScanJet Pro 2000 s1 roller replacement kit (L2760A)		

Ordering Information

Number Description L2759A HP ScanJet Pro 2000 s1 Sheet-feed Scanner

HP Care Packs

Number	Description
U9JQ3E	HP 3 year Exchange Hardware Support for

ScanJet Pro 2xxx U9105F HP 3 year Return to Depot Hardware Support for ScanJet Pro 2xxx

Protect your investment with HP Care Pack. Let HP certified engineers resolve your technical issues. For more details on HP Care Pack, go to hp.com/go/cpc

HP Inc. offices

Australia	(613) 8833 5000	hp.com.au
China	(010) 6564 3888	hp.com.cn
Hong Kong	(852) 3077 2688	hp.com.hk
India	(80) 2612 9000	hp.com/in
Indonesia	(62-21) 5799	hp.com/id
	1088	
Korea	(02) 2199 0114	hp.co.kr
Malaysia	(603) 2332 3333	hp.com.my
New Zealand	(09) 918 9555	hp.co.nz
Philippines	(632) 888 5900	hp.com/ph
Singapore	(65) 6275 3888	hp.com.sg
Taiwan	(02) 3789 9900	hp.com.tw
Thailand	(662) 353 9500	hp.com/th
Vietnam	(848) 3823 4151	hp.com/vn

For the following countries, please fax your gueries to(65) 6275 6707 Bangladesh, Bhutan, Brunei, Cambodia, Maldives, Nepal, Pakistan, Sri Lanka

Supported paper

Contact HP via phone: Asia: 65 6253 8500

Solutions

For more solutions information, please visit hp.com/go/gsc
















To learn more, visit hp.com







¹ With input and output trays folded and covers closed

² Actual speeds may vary depending on scan resolution, connectivity type, computer performance and application software.